




- Material: Polyamid PA6 GF30

- Lieferfarbe: lichtgrau (RAL 7035)
 - 90°-Winkel, Auflagefläche im Innengewinde für Druckring und Dichtring

- Schutzart: bis IP 68 max.
 - Temp.bereich: -20°C bis +80°C



Art.-Nr.	A/B Gewinde	L/mm mm	SW	/mm Breite	H/mm Höhe	Di/mm	VE Stück	Netto € pro 100 Stück		
								ab 10 St.	ab 100 St.	ab 200 St.
mit metrischem Gewinde										
58116	M16 x1,5	12,0	19	30,0	38,0	12,2	100	78,12	74,57	71,02
58120	M20 x1,5	12,0	23	36,0	42,0	16	50	93,22	88,99	84,75
58125	M25 x1,5	12,0	29	44,0	48,5	21	50	113,96	108,77	103,59
58132	M32 x1,5	14,0	36	53,0	57,5	27,6	25	118,62	113,23	107,84
58140	M40 x1,5	14,0	44	64,0	67,0	35	10	136,64	130,43	124,22
mit PG-Gewinde										
58009	PG 9	11	-		30	11,5	100	81,69	67,62	59,64
58011	PG 11	11	-		33	14,5	50	83,06	70,25	61,11
58013	PG 13,5	11,5	-		35,5	16	50	102,82	85,16	71,72
58016	PG 16	11,5	-		38,5	18,5	50	110,36	91,98	76,55
58021	PG 21	13	-		46	24	25	176,10	147,20	128,10
58029	PG 29	15	-		59	32	10	191,10	159,85	139,10