

Halbverschraubung HKV

Polyamid




- Material: Polyamid, glasfaserverstärkt PA6 GF30

- Lieferfarbe: lichtgrau (RAL 7035)

- Temp.bereich: -30°C bis +100°C

- metrische Verschraubung nach EN 60423



| Art.-Nr. | Gewinde | L/mm | Gew.L. mm | VE Stück | Netto € pro 100 Stück | | | | |
|-------------------------------|----------|------|--------------|-------------|-----------------------|------------|-------------|--------|-------|
| | | | | | ab 20 St. | ab 100 St. | ab 200 St. | | |
| mit metrischem Gewinde | | | | | | | | | |
| 25312 | M12 x1,5 | 8,5 | 13 | 13,5 | 7 | 100 | 15,65 | 14,57 | 12,60 |
| 25316 | M16 x1,5 | 8,5 | 17 | 13,5 | 10 | 100 | 18,36 | 17,08 | 13,00 |
| 25320 | M20 x1,5 | 10,5 | 21 | 15,5 | 13,5 | 100 | 22,91 | 21,32 | 16,70 |
| 25325 | M25 x1,5 | 12,5 | 26 | 18,5 | 20 | 50 | 26,95 | 25,09 | 23,28 |
| 25332 | M32 x1,5 | 14,5 | 34 | 20,5 | 26 | 50 | auf Anfrage | | |
| 25340 | M40 x1,5 | 16,0 | 42 | 24 | 34 | 50 | auf Anfrage | | |
| mit PG-Gewinde | | | | | | | | | |
| 25607 | PG 7 | 8,5 | 13 | 13,5 | 7 | 100 | | | |
| 25609 | PG 9 | 8,5 | 16 | 13,5 | 9,5 | 100 | 16,43 | 15,30 | 14,23 |
| 25611 | PG 11 | 10 | 19 | 15 | 11,5 | 100 | 19,28 | 17,93 | 16,67 |
| 25613 | PG 13,5 | 10,5 | 21 | 15,5 | 13 | 100 | 24,06 | 22,39 | 20,81 |
| 25616 | PG 16 | 11,5 | 23 | 17,5 | 15,5 | 50 | 28,30 | 26,34 | 24,50 |
| 25621 | PG 21 | 13,5 | 30 | 19,5 | 20,5 | 50 | 47,13 | 43,84 | 40,76 |
| 25629 | PG 29 | 14,5 | 40 | 21,5 | 27 | 20 | 111,03 | 102,17 | 95,00 |