

## Verschraubung MAXL


Messing



- Messing CuZn39Pb3, galvanisch vernickelt
- Dichteinsatz aus Neopren
- O-Ring: Nitril

- Anschlussgewinde: nach EN 60423
- montagefreundlich

- Temp.-Ber.: -40°C bis + 100°C
- Schutzart: IP 68



Art.-Nr.	A	ØC mm	L mm	SW mm	H	VE Stück	Netto € pro Stück ab 1 St..
<b>mit metrischem Gewinde</b>							
101012-XL	M12 x 1,5	4 - 8	7,0	17	33,0	1	3,90
101016-XL	M16 x 1,5	7 - 12	7,0	20	30,0	1	4,00
101020-XL	M20 x 1,5	9 - 16	7,0	24	34,0	1	4,20
101025-XL	M25 x 1,5	9 - 16	8,0	24/30	35,0	1	5,10
101026-XL	M25 x 1,5	13 - 20,5	8,0	30	36,0	1	5,15
101032-XL	M32 x 1,5	13 - 21	8,5	30/36	36,5	1	5,90
101033-XL	M32 x 1,5	16 - 27	8,5	40	53,5	1	8,90
101040-XL	M40 x 1,5	21 - 34	8,5	48	59,5	1	10,60
101050-XL	M50 x 1,5	28 - 41	9,5	55	65,5	1	18,90
101064-XL	M63 x 1,5	39 - 54	10,5	70	78,5	1	43,50
101075-XL	M75 x 1,5	48 - 65	11,5	85	93,5	1	79,80
101080-XL	M80 x 2,0	55 - 74	12,0	95	104,0	1	99,10
101090-XL	M90 x 2,0	65 - 83	12,0	110	113,0	1	163,90
1010100-XL	M100 x 2,0	74 - 93	12,0	120	113,0	1	205,90

**Staffel-Nettopreise auf Anfrage: Infotelefon +49 (0)9120 6429**