

O-Dichtring O


NBR



- Nitrilkautschuk NBR

- zur besseren Abdichtung am Anschlussgewinde

Temp.bereich: -30°C bis +100°C



Art.-Nr.	Größe	D mm	Da mm ø	Di mm ø	VE Stück	Netto € pro 100 Stück				
						ab 50 Stück	ab 100 St.	ab 500 St.	ab 1000 St.	
für metrische Gewinde										
35712	M 12	1,5	12	9	100	6,30	5,86	5,09	4,81	
35716	M 16	1,5	16	13	100	6,30	5,86	5,09	4,81	
35720	M 20	1,5	21	18	100	7,90	6,73	5,85	5,52	
35725	M 25	2	25	21	100	7,90	6,73	5,85	5,52	
35732	M 32	2,5	34	29	50	8,10	7,23	6,29	5,93	
35740	M 40	2	41	37	50	8,10	7,23	6,29	5,93	
35750	M 50	2,5	52	47	50	13,75	12,28	10,68	10,07	
35763	M 63	3	66	60	50	14,52	12,96	11,27	10,63	
für PG-Gewinde										
35307	PG 7	1,5	13	10	100	7,14	5,69	5,31	4,81	
35309	PG 9	2	17	13	100	7,14	5,69	5,31	4,81	
35311	PG 11	2	20	16	100	7,46	6,38	6,07	5,48	
35313	PG 13,5	2	22	18	100	7,46	6,38	6,07	5,48	
35316	PG 16	2	24	20	100	8,30	7,09	6,66	6,02	
35321	PG 21	2	28	24	100	8,30	7,09	6,66	6,02	
35329	PG 29	2	37	33	100	14,28	13,21	12,35	11,11	
35336	PG 36	2,5	47	42	50	15,57	13,85	12,99	11,81	
35342	PG 42	2,5	53	48	50	20,18	18,04	16,85	15,57	
35348	PG 48	3	60	54	50	23,19	20,66	19,33	17,71	

auf Anfrage: auch als Viton-Dichtring (-25°C bis +200°C) lieferbar!