




# O-Dichtring O



## AUFBAU

Material: Nitrilkautschuk NBR

## EIGENSCHAFTEN

Temperaturb.: -30°C bis +100°C

| Art.-Nr.                                                 | A<br>Gewinde | D in mm | Da in mm<br>Gewindelänge | Di in mm<br>Höhe | VE<br>Stück |
|----------------------------------------------------------|--------------|---------|--------------------------|------------------|-------------|
| <b>Mit metrischem Gewinde</b>                            |              |         |                          |                  |             |
| 35712                                                    | M12          | 1,5     | 12,0                     | 9,0              | 100         |
| 35716                                                    | M16          | 1,5     | 16,0                     | 13,0             | 100         |
| 35720                                                    | M20          | 1,5     | 21,0                     | 18,0             | 100         |
| 35725                                                    | M25          | 2,0     | 25,0                     | 21,0             | 100         |
| 35732                                                    | M32          | 2,5     | 34,0                     | 29,0             | 50          |
| 35740                                                    | M40          | 2,0     | 41,0                     | 37,0             | 50          |
| 35750                                                    | M50          | 2,5     | 52,0                     | 47,0             | 50          |
| 35763                                                    | M63          | 3,0     | 66,0                     | 60,0             | 50          |
| <b>Mit PG-Gewinde</b>                                    |              |         |                          |                  |             |
| 35307                                                    | PG 7         | 1,5     | 13,0                     | 10,0             | 100         |
| 35309                                                    | PG 9         | 2,0     | 17,0                     | 13,0             | 100         |
| 35311                                                    | PG 11        | 2,0     | 20,0                     | 16,0             | 100         |
| 35313                                                    | PG 13,5      | 2,0     | 22,0                     | 18,0             | 100         |
| 35316                                                    | PG 16        | 2,0     | 24,0                     | 20,0             | 100         |
| 35321                                                    | PG 21        | 2,0     | 28,0                     | 24,0             | 100         |
| 35329                                                    | PG 29        | 2,0     | 37,0                     | 33,0             | 100         |
| 35336                                                    | PG 36        | 2,5     | 47,0                     | 42,0             | 50          |
| 35342                                                    | PG 42        | 2,5     | 53,0                     | 48,0             | 50          |
| 35348                                                    | PG 48        | 3,0     | 60,0                     | 54,0             | 50          |
| Auf Anfrage: Auch als Viton-Dichtring (-25°C bis +200°C) |              |         |                          |                  |             |