



Mehrfach-Dichteinsätze ME

für Elite-PN, Elite-PK und Elite-MS



Material: Thermoplastisches Elastomer TPS
Aufbau: Zur Durchführung mehrerer Einzelkabel

Temperaturbereich: -30°C bis +100°C

Art.-Nr.	A Gewinde	n x Di in mm Klemmbereich	Da in mm Gewindelänge	H in mm Höhe	VE Stück
Für metrisches Gewinde					
35	M12	2 x 1,6	8,5	6,6	100
353212	M12	3 x 2,3	8,5	6,6	100
351212	M12	4 x 2,0	8,5	6,6	100
350616	M16	2 x 4,0	11,7	7,6	50
350716	M16	2 x 4,5	11,7	7,6	25
350916	M16	4 x 2,3	11,7	7,6	10
350816	M16	4 x 3,5	11,7	7,6	5
350920	M20	2 x 4,0	15,1	7,5	5
351020	M20	2 x 6,0	15,1	7,5	5
351120	M20	4 x 5,0	15,1	7,5	100
351125	M25	2 x 6,0	19,8	9,3	100
351025	M25	2 x 8,0	19,8	9,3	100
351625	M25	3 x 4,0	19,8	9,3	50
351325	M25	3 x 6,0	19,8	9,3	25
351225	M25	3 x 7,0	19,8	9,3	10
351725	M25	4 x 5,0	19,8	9,3	100
351825	M25	4 x 6,0	19,8	9,3	50
351425	M25	4 x 6,5	19,8	9,3	25
351925	M25	5 x 4,0	19,8	9,3	10
351525	M25	6 x 4,0	19,8	9,3	100
351232	M32	2 x 8,0	25,1	12,5	100
351332	M32	3 x 8,0	25,1	12,5	100
351432	M32	4 x 7,0	25,1	12,5	50
351032	M32	4 x 8,0	25,1	12,5	25
351532	M32	4 x 8,5	25,1	12,5	10
351632	M32	6 x 4,0	25,1	12,5	100
351132	M32	6 x 6,0	25,1	12,5	100
351140	M40	4 x 10,0	32,3	15,0	50
351340	M40	5 x 8,5	32,3	15,0	25
351240	M40	8 x 6,5	32,3	15,0	10
Für PG-Gewinde					
351409	PG 9	2 x 3,0	10,6	7,5	100
351411	PG 11	2 x 4,0	13,3	8,5	100
351511	PG 11	3 x 4,0	13,3	8,5	100
351413	PG 13,5	2 x 6,0	15,3	8,5	50
351513	PG 13,5	3 x 4,0	15,3	8,5	50
351416	PG 16	2 x 4,0	17,4	9,0	50
351516	PG 16	2 x 6,0	17,4	9,0	50
351616	PG 16	3 x 4,0	17,4	9,0	50
351716	PG 16	3 x 6,0	17,4	9,0	50
351816	PG 16	4 x 5,0	17,4	9,0	50
351916	PG 16	5 x 4,0	17,4	9,0	50
351421	PG 21	2 x 8,0	22,2	11,0	25
351621	PG 21	3 x 7,0	22,2	11,0	25
351721	PG 21	3 x 8,0	22,2	11,0	25
351821	PG 21	4 x 7,0	22,2	11,0	25
351429	PG 29	5 x 8,5	29,8	13,0	25