

Verschlusschraube VS Standard



AUFBAU

Material: Polyamid PA6
Gewinde: Metrisch n. DIN EN 60423
PG nach DIN 40430

EIGENSCHAFTEN

Schutzart: IP54
Temperaturbereich: -20°C bis +100°C

Art.-Nr.	A Gewinde	L /mm Gewindelänge	H /mm Höhe	Da /mm Ø Kopf	VE Stück
Mit metrischem Gewinde (auch in schwarz lieferbar: Art.-Nr. + '-sw')					
57112	M12x1,5	6,0	9,0	17,0	100
57116	M16x1,5	6,0	10,0	22,0	100
57120	M20x1,5	6,0	10,0	25,5	100
57125	M25x1,5	7,0	11,5	31,0	50
57132	M32x1,5	8,0	12,5	37,0	50
57140	M40x1,5	9,0	12,5	46,0	50
57150	M50x1,5	10,0	15,0	60,0	25
57163	M63x1,5	12,0	18,0	75,0	25
Mit PG-Gewinde					
57007	PG 7	6,0	10,0	15,0	100
57009	PG 9	6,0	10,5	19,0	100
57011	PG 11	6,5	11,5	22,0	100
57013	PG 13,5	6,0	12,5	25,0	100
57016	PG 16	6,5	12,5	27,0	100
57021	PG 21	8,0	14,5	33,0	100
57029	PG 29	8,0	18,0	44,0	50
57036	PG 36	10,0	21,5	55,0	25
57042	PG 42	10,0	24,5	62,0	25
57048	PG 48	12,0	25,5	69,0	25

Erhältlich in:

Art.Nr.

Lichtgrau
RAL 7035

Art.Nr. +
-sw

Schwarz
RAL 9005

